

Technical Report No. 65.190.12.00104.01C Rev. 00 Dated 2022-01-26

Client: Topfinger Equipment (Shenzhen) Co.,Ltd

No.101, Niumianling Cun, Sifangpu Community, Pingdi Distreet, Longgang District, Shenzhen City

Test subject: Product:CROWD BARRIER

Type:ESI05CB001

Test specification: According to the client's requirements.

Details see Clause 3.

Purpose of examination: Test according to the test specification.

Test result: Details see the test result in Clause 3.

This technical report may only be quoted in full. Any use for advertising purposes must be granted in writing. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production.

Engineer: Calvin Yang

Technical Report No.: 65.190.12.00104.01C



1 Description of the test subject

1.1 Function


Manufacturer's specification for intended use, STAGE

1.2 Technical Data

Dimension (L x W x H): 1250 mm x 1000 mm x 1250 mm

Weight: 28,0 kg

1.3 Product Photos











2 Order

2.1 Date of Purchase Order

2022-01-15

2.2 Receipt of Test Sample

2022-01-24

2.3 Date of Testing

From 2022-01-24 to 2022-01-26

2.4 Points of Non-compliance or Exceptions of the Test Procedure

NA



3 Test Results

| Clause | Requirement Test | Remark | Verdict |
|--------|--|---|---------|
| 1 | Loading test A test vertical load F ₂ of 5000N shall be distributed uniformly applied to the whole surface of the platform, then applied a horizontal force F ₁ of 2000N to the stage tested according to Figure 1. After removal of the test load, the barrier shall not show any visible damages such as cracks, indentations etc. | No visible damage was found after test. | Р |
| | | | |
| | Figure 1 | | |

TÜV Product Service Ltd. Guangzhou Branch TÜV SÜD Group

Engineer:

Calvin Yang

Technical Report Checked:

Filippo Wei